

Crimp ring terminal CU, insulated / PVC

For quick and easy assembly, our ring terminals feature an easy entry system. This speeds up assembly and minimises errors.



Technical Data:

Materials:

Colors:

Design:

Operating temperature:

Max. voltage:

Max. current:

Standards:

Copper (electro tin-plated)

Insulation: PVC (vinyl)

red, blue, yellow

insulated

-10 °C to +75 °C

600V

red 19A

blue 27A

yellow 48A

REACH, RoHS



Size chart and technical drawing on page 2

Size Chart

Item no.	Color	Cross-section [mm ²]	L [mm]	D1 [mm]	D2 [mm]	D3 [mm]	A1 [mm]	B [mm]	PU [pcs]
54001	red	0.5–1	16	1.6	4.1	3.2	11.5	6	100
54002	red	0.5–1	16	1.6	4.1	3.7	11.5	6	100
54003	red	0.5–1	17	1.6	4.1	4.3	11.5	8	100
54004	red	0.5–1	18	1.6	4.1	5.3	11.5	10	100
54005	red	0.5–1	20	1.6	4.1	6.5	11.5	11	100
54006	red	0.5–1	22	1.6	4.1	8.4	11.5	14	100
54007	red	0.5–1	24	1.6	4.1	10.5	11.5	18	100
54008	blue	1.5–2.5	17	2.3	4.5	3.2	11.5	6	100
54009	blue	1.5–2.5	17	2.3	4.5	3.7	11.5	6	100
54010	blue	1.5–2.5	18	2.3	4.5	4.3	11.5	8	100
54011	blue	1.5–2.5	20	2.3	4.5	5.3	11.5	10	100
54012	blue	1.5–2.5	22	2.3	4.5	6.5	11.5	11	100
54013	blue	1.5–2.5	23	2.3	4.5	8.4	11.5	14	100
54014	blue	1.5–2.5	25	2.3	4.5	10.5	11.5	18	100
54015	yellow	4–6	20	3.6	6.8	4.3	13	8	100
54016	yellow	4–6	21	3.6	6.8	5.3	13	10	100
54017	yellow	4–6	22	3.6	6.8	6.5	13	11	100
54018	yellow	4–6	25	3.6	6.8	8.4	13	14	100
54019	yellow	4–6	27	3.6	6.8	10.5	13	18	100

