

Data sheet:

Edge clips for corrugated conduits

Our high-quality edge clips hold your corrugated pipe reliably wherever space is tight, where drilling, welding or gluing is not possible. The small dimensions of the clips leave more space for the corrugated pipe in confined installation spaces. When selecting the right corrugated conduit clip, please consider the outer diameter of the bundled goods and the profile thickness.

Technical data:

Material:	Polyamide 6.6 / PA6.6 HS (heat-stabilised, weather-resistant, impact-resistant)
Colours:	black
Insert temperature:	-40 °C to + 120 °C (briefly up to +140 °C)
Metal clip:	Spring steel, hardened and coated surface (fulfils the highest corrosion protection requirements)
Fire protection properties:	Underlying material self-extinguishing
UV resistance:	very good
Chemical resistance:	good resistance to bases, alcohols, oils, greases, fuels/ spring steel corrosion-resistant (hardened surface)
Standards:	REACH, RoHS



Article:

Article no.	Variation	Nominal diameter [NW]	For edge / profile width [mm]
38900	lengthwise to the profile, on the top of the bracket	4,5	0,7 – 3,0
38901	lengthwise to the profile, on the top of the bracket	7,5	0,7 – 3,0
38902	lengthwise to the profile, on the top of the bracket	17	0,7 – 3,0
38903	lengthwise to the profile, on the top of the bracket	4,5	3,0 – 6,0
38904	lengthwise to the profile, on the top of the bracket	13	3,0 – 6,0
38905	at right angles to the profile, on the top of the bracket	4,5	0,7 – 3,0
38906	at right angles to the profile, on the top of the bracket	10	0,7 – 3,0
38907	at right angles to the profile, on the top of the bracket	13	0,7 – 3,0
38909	lengthwise to the profile, to the side of the bracket	4,5	0,7 – 3,0
38910	lengthwise to the profile, to the side of the bracket	10	0,7 – 3,0
38911	lengthwise to the profile, to the side of the bracket	13	0,7 – 3,0
38912	lengthwise to the profile, to the side of the bracket	4,5	3,0 – 6,0
38913	lengthwise to the profile, to the side of the bracket	7,5	3,0 – 6,0
38914	lengthwise to the profile, to the side of the bracket	10	3,0 – 6,0
38908	lengthwise to the profile, to the side of the bracket	2 x 10	0,7 – 3,0

Example images of the designs:



lengthwise / top



at right angles / top



lengthwise / on the side



lengthwise / on the side / 2 x 10

More information at: <https://www.emc-direct.de> / info@emc-direct.de / Phone: +49 (0)2369 – 98469 -15

Version: 1 (english version) / 23.10.2024